

NeuroTherm[®]

RF for Pain Management

NEW
ECONOMICAL

Economical

The NT500 provides the most functionality for the lowest price, making it the most economical RF lesion generator on the market.

Portable

Working at multiple facilities in the same week or day? The NT500 is small and lightweight enough to easily take with you wherever you go.

Easy-to-Use

The new intuitive design allows you to perform your RF procedures with minimal orientation both in continuous and pulsed RF modes.

Pulse and Pulse Dose™

The NT500 is available with continuous thermal RF and a choice of either Pulsed or Pulse Dose™ RF modes.

NT500 Radiofrequency Lesion Generator



RFG-NT-500

DISPERSIVE

NeuroTherm®

RF for Pain Management

NEW PORTABLE

The New NT500 RF Lesion Generator

The new NT500 RF Lesion Generator is a low-cost yet full-featured device. It weighs just under 15lbs and fits into a handy over-the-shoulder carrying case making it the most portable RF generator on the market. Its sleek intuitive design makes it easy to use allowing you to execute RF procedures very quickly, with minimal staff orientation.



CC-H-500

Technical Specifications

Dimensions

12 x 6.5 x 14.5 inches (30 x 16 x 36.5 cm)
14.8 lbs (6.75 kg)

Impedance Monitor

Digital Display 0-2000 ohms (in 1Ω steps)
Reads biological impedance in standby mode

Temperature Monitor

Automatically adjusts RF power to not exceed set temperature
Set for RF 70, 80, 90°C
Range 30-100°C

Stimulation

Voltage Amplitude 0-3 volts (in 0.01V steps)
Pulse Rates 2, 50, 100 pulses/sec (Default setting: 50Hz for 110V, 100Hz for 230V)
Pulse Width 1 mSec
Wave Form Biphasic pulses. Negative pulse leading

Lesion Mode

Power Output Continuously variable.
25 watts maximum into 200Ω
RF Frequency 480KHz (±10%) sine wave
Voltage Range 0-90V
Current Range 0-800mA
Audible Tone 2s tone when lesion complete

Timer/Count

Time set button cycles timer through 30, 60, 90, 120, 240s. Count set cycles through 120, 240, 360, 480 counts. Default timer settings are 60s for lesion and 120s for pulsed. Default count setting 240. Pressing start initiates timing/counting.

Pulsed/Pulsed Dose RF RF bursts of 20ms at a frequency of 2Hz
Pulse Temp Limit 42°C (changable to no limit)
Pulse Dose Limit 42°C

Patient Connections

Standard four-pin lemo for the active connection
Standard 4mm shrouded banana jack for the reference connection

Safety Features

RF power cannot be delivered unless the RF Power Control is first set to the OFF position.

Lesion power also will be cut off if the measured temperature exceeds 95°C or if the system detects a short circuit or low patient impedance.

Standards

UL 60601-1
IEC60601-1
CAN/CSA C22.2
No. 601.1 and
IEC60601-2-2

Warranty

One year

Accuracy

Temperature ±3°C using standardized electrodes
Pulse Rate ±5% in stimulation mode
Lesion Accuracy ±10% voltage, current, frequency

NT500 RF Lesion Generator System



RFG-NT-500

NeuroTherm®

2 DeBush Ave., Suite A-2 • Middleton, MA 01949 • USA
1-888-655-3500 • (978) 777-3916 • (978) 777-5121 FAX
usasales@neurotherm.com

429 Brighton Road • Croydon, Surrey CR2 6EU • UK
+44 (0) 20 8660 4374 • +44 (0) 20 8660 9418 FAX
sales@neurotherm.com

www.neurotherm.com

NeuroTherm is a registered trademark of NeuroTherm Inc.
©2007 NeuroTherm Inc. August 2007
C0711-0708 USA

Distributed by:

